


SUSPENSION KIT

Magnetic kit

Drill-free kit for steel ceilings and structures: neodymium magnet with M6 thread, cable and panel fixing.



TECHNICAL DATA

Cable	7x7 galvanised steel · optional clear sheath
Cable range	Ø1.5 mm
Material	Neodymium magnet in steel cup
Thread / fixing	M6
Working load	Pending test
Cable length	1000 · 2000 · 3000 mm or custom
Finishes	Nickel (NI) · black (BK) · white (WH)
Supply	Assembled and labelled · box of 8 kits

INSTALLATION

1

Clean the steel surface: free of grease and dust.

2

Place the magnet gradually, without impact.

3

Minimum 5 mm sheet without thick paint; usable force is 1/5 of the force measured on site.

KIT CONTENTS

ITEM	CODE	DESCRIPTION	QTY
1	DS-MG-M6	Neodymium magnet with M6 thread	1
2	DS-C15	7x7 cable Ø1.5 mm	1
3	DS-G-M6	M6 gripper	1

ORDER CODE

DS-M-M6-15-2000-NI

series · fixing · cable Ø · length mm · finish
NI nickel · BK black · WH white

DSUSPEND LABORATORY TESTS

Tensile test to failure	☐ PENDING
Slip under load	☐ PENDING
Salt spray ISO 9227	☐ PENDING
Adjustment cycles	☐ PENDING

SAFETY



Static loads only



No chlorine or corrosive areas



No grease or lubricants



Never use frayed cable



Maximum 60° inclination



Do not paint components

Provisional document: data will be completed with our laboratory tests. Images for reference only. Data subject to change without notice.